



FOR GOOD REASONS

panDOMO® SP-CR

Maintenance and Repair Cleaner

For periodically cleaning and care for all PANDOMO® Floors, which have been treated with PANDOMO® SP-SL Stoneoil, PANDOMO® SP-GS Sealer or PANDOMO® SP-PS water based PU-Sealer.

Removes stains

Repairs and protects with protective film

Low foam forming

Does not build up any cleaning layers

Concentrate

High yield



Reg. No. 37344

Manufacturer
with certified quality system
as per DIN EN ISO 9001

ARDEX GmbH
58430 Witten · P.O. Box 6120
GERMANY
Telephone: +49 (0) 23 02/664-0
Telefax: +49 (0) 23 02/664-437
kundendienst@ardex.de
www.ardex.de

panDOMO® SP-CR

Maintenance and Repair Cleaner

Use:

For periodically cleaning and care for all PANDOMO® Floors, which have been treated with PANDOMO® SP-SL Stone oil, PANDOMO® SP-GS Sealer or PANDOMO® SP-PS water based PU-Sealer.

Only in the interior. Can be used for machine cleaning.

Properties:

- Removes stains
- Repairs and protects with protective film
- Low foam forming
- Does not build up any cleaning layers

The incorporated cleaning components re-move the stains from the floors and will keep them in the cleaning water. The maintenance components will stay on the surface but will not form a layer.

Application:

a) Standard Cleaning:

Swipe the floor with a broom or with the brush side of the vacuum cleaner to remove dirt and sand because this could act as a grinding paper.

Dilute PANDOMO® SP-CR (approx. 50 ml for 8 Liter water). Wipe the floor mist wet and let them dry. Do not rinse with clean water. Please use two buckets on for the PANDOMO® SP-CR, and the other to take the dirty water.

b) Repairing of minor defects:

Dilute PANDOMO® SP-CR (approx. 200 ml for 8 Liters water). Wipe the floor wet. Minor scratches and mat areas will disappear or hardly visible. Stripes which may occur after drying can be wiped off with a dry cloth. The buildup film will be removed through cleaning an wiping.

Important notice:

Do not use PANDOMO® SP-CR with other cleaning agents. Do not traffic the floor while still wet.

General:

Do not saturate the floor with water. Only apply a thin water film. Avoid heavy traffic within the first days of use. This will result in a longer lasting floor.

Full use of the floors only after complete drying of the Oil (approx. after 2-3 days depending on the climatical conditions on site).

Health and safety/disposal:

Keep out of reach from children

Container and content/dispose according to local/regional/national and international laws.

Technical data according to ARDEX quality standards:

Material requirement:	approx. 10 – 20 ml/m ²
Density:	approx. 1,0 g/cm ³
PH-Value:	approx. 8,5
Appearance:	liquid, clear, yellowish
Water solveable:	completely
Application temperature:	approx. + 15 - + 25°C
Marking acc. GHS/CLP:	None
Marking acc. GGVSEB/ADR:	None
GISCODE:	GU 40
Packaging:	Plastic container 5 L net Plastic bottle 1 L net
Storage:	cool, but free from frost Close tightly after usage
Shelf life:	can be stored for approximately 24 months in dry rooms in unopened packaging

